Foodmax Basic 15, 32, 68

Lubricating white paraffin oil

Description

Paraffin food grade oil for general lubrication purposes. Can be used in the authorized industrial operations wherever there is the possibility of food contact (for both humans or animals). Foodmax Basic can be used as a general lubricant in various applications in the food processing industry. Select the right viscosity for the right application. Gives excellent results as general lubricant in the textile, knitwear, food and tin industry, generally whenever very high cleanliness level is requested. Foodmax Basic is NSF H-1, 3-H and HX-1approved.

Properties

- Colourless, odourless and tasteless white paraffin oil
- Good lubricating capacity
- Good adherence
- Provides a clean non staining and non contaminating lubrication
- NSF H-1, 3-H and HX-1 approved
- Can be used as lubricant and mould releaser in the food industry

Applications

- Manual with oiler
- Automatic lubrication by oil dripping, brush or spraying

Typical performance data

	15	32	68
Colour, saybolt	+30	+30	+30
Density @ 25 °C	0.820-0.840	0.828-0.850	0.855-0.863
Viscosity @ 40 °C	14-18 cSt	27-33 cSt	60-70 cSt
Flash point °C, min	180	190	210
Pour point °C max	-9	-9	-6
USP/BP	Passes	Passes	Passes
FDA 21 CFR 172.878	Passes	Passes	Passes
FDA 21 CFR 178.3620 a	Passes	Passes	Passes

All performance data on this Technical Data Sheet are indicative only and can vary during production

Matrix Specialty Lubricants